




NUMINOS® PROJECTOR L

recessed ceiling light, 2700 K, 20°, cylindrical, black / white

Outstanding LED technology, harmonious design and a diverse range of applications: the NUMINOS® PROJECTOR recessed ceiling light effectively illuminates elegant living rooms, shops, restaurants, hotels and museums. The spot emits a high-quality light with different colour temperatures (2700K/3000K/4000K) and half-peak divergence (20°/40°/55°) that is suitable for various projects. The beam can be tilted and rotated to light up a large area. The housing is available in black or white, the decorative reflector in black, white or chrome.



TECHNICAL DATA

Item no.	1007030
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	25.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2250 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22
LXXBXX data	L80B50
Service life	50000 h
Risk Group	1
Length	13 cm
Diameter	10 cm
Net weight	0.95 kg

Light Source

791800	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA for Numi- nos Downlight Serie
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1006460	LED bridge driver , 42W, 700mA for NUMINOS®, including radio interface for RF module, DALI
1004794	NUMINOS® L , diffuser Ellipse
1006454	RF module Casambi for LED bridge driver , single colour
1006199	RF module Zigbee for DALI LED bridge driver , single colour
1004070	LED driver , 40W 700mA DALI
1004797	NUMINOS® L , diffuser Wabe
1004065	LED driver , 30W 700mA

Gross weight	1.017 kg
Shape of cut-out	round
Installation depth	15 cm
Installation diameter	13 cm
BIG WHITE Page	93