




## QUADRULO

wall-mounted light, 3000K, anthracite/brown

Aluminium LED wall light from the QUADRULO range with a clear illuminated area. Thanks to its high IP rating, this light is suitable for outdoor use and comes with or without a motion sensor. The electrical connection can be connected directly to the 230V mains power supply.



## TECHNICAL DATA

Item no.	1007207
IP Code	IP 55
Impact resistance class	IK 04
Assembly	Surface
Assembly details	Wall
Number of through-wires	20
Primary nominal voltage	100-277V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	7.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	103
Number of luminaires at LS C16A	103
Level of inrush current	5 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.01
Lumen	280 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50

Light Source

916332	
--------	---

Service life	30000 h
Risk Group	0
Width	12.5 cm
Height	25 cm
Depth	13.2 cm
Net weight	0.97 kg
Gross weight	1.038 kg
BIG WHITE Page	744