



Set consisting of 12 x 1007095 UNIVERSAL DOWNLIGHT PHASE IP65 38° and 1007096 UNIVERSAL DOWNLIGHT cover IP65 black R

The UNIVERSAL DOWNLIGHT Multipack contains 12 of the UNIVERSAL DOWNLIGHT PHASE recessed lights with matching covers in black. An all-round carefree package that makes planning even easier with our UNIVERSAL DOWNLIGHT. Due to its narrow beam angle of 38 degrees, the recessed light provides a targeted beam of light. The IP65 protection rating also protects it from water jets. The CCT switch allows the color temperature to be selected before installation (2700/3000/4000/6000K), giving you maximum flexibility on the construction site. The choice of total wattage - 5W or 8W - is just as easy. True-to-life colour reproduction is guaranteed thanks to CRI90. The corresponding Quick Connector Box rounds off the overall picture and makes installation of these recessed lights easier than ever.

TECHNICAL DATA

| | |
|---------------------------------|----------------------------|
| Item no. | 1007271 |
| IP Code | IP20/IP65 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Number of through-wires | 10 |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 60/90 mA |
| Safety class | II |
| Wattage | 8 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 60 |
| Number of luminaires at LS C16A | 150 |
| Level of inrush current | 3 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 560/610/680/640 lm |
| Colour temperature | 2700/3000/4000/6500 Kelvin |

Light Source

1807465



| | |
|-----------------------|---------|
| Beam angle | 38 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 28 |
| LXXBXX data | L70B50 |
| Service life | 35000 h |
| Risk Group | 0 |
| Height | 4.85 cm |
| Diameter | 8.8 cm |
| Net weight | 3 kg |
| Gross weight | 3.21 kg |
| Shape of cut-out | round |
| Installation depth | 5.5 cm |
| Installation diameter | 6.8 cm |
| BIG WHITE Page | 208 |