




MEDO® 30

wall- and ceiling-mounted light, round,
2700/3000/4000 K, 12 W, trailing-edge phase, 110°,
white

The new MEDO® sets standards and impresses with a longer service life, better energy efficiency and a higher in-direct light component. The improved protection code IP50 and an outstanding CRI >90 colour reproduction index ensure exceptional quality. Three elegant casing colours and a CCT switch that enables you to choose between 2700 K, 3000 K and 4000 K lets you personalise your lighting situation. And thanks to EasyBase, installation is as simple as it is fast.



TECHNICAL DATA

Item no.	1007317
Number of different light outlets	2
IP Code	IP50
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	20
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Operating efficiency (LOR)	0.89
Number of luminaires at LS B16A	71
Number of luminaires at LS C16A	89
Level of inrush current	6.5 A
Duration of inrush current	40 µs
Lumen	1000/1050/1150 lm
Colour temperature	2700/3000/4000 Kelvin
Beam angle	110 °

Light Source

1900642	
---------	---

Accessories

1001952	MEDO 5 m suspension , black
1001950	MEDO 5 m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5 m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Color	white/white
CRI	90
UGR ≤	25
Service life	50000 h
Risk Group	1
Height	9.2 cm
Diameter	28 cm
Net weight	1.488 kg
Gross weight	2.127 kg
BIG WHITE Page	250