




NEW TRIA® 75

recessed ceiling light, 2700 K, 38°, IP 20, round, black


Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 75 are available as a complete set. The integrated LED MODULE, which is available with different light colours (2700 K/3000 K) and a beam angle of 38°, provides lighting design options. In black or white, the round housing blends harmoniously into any room ambience. And thanks to the 75 mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------------|
| Item no. | 1007402 |
| Rotating or tilting | tiltable |
| IP Code | IP20 |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 200 mA |
| Safety class | II |
| Wattage | 8.3 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 88 |
| Number of luminaires at LS C16A | 149 |
| Level of inrush current | 3 A |
| Duration of inrush current | 30 µs |
| Lumen | 705 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 38 ° |
| Color | black |
| Risk Group | 1 |
| Height | 4 cm |
| Diameter | 9.3 cm |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 869193 |  | Net weight | 0.234 kg |
| | | Gross weight | 0.279 kg |
| | | Shape of cut-out | round |
| | | Installation depth | 4 cm |
| | | Installation diameter | 7.5 cm |
| | | BIG WHITE Page | 107 |