




NEW TRIA® 68

recessed ceiling light, 3000 K, 38°, IP 20 / IP 65, round, white


Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are available as a complete set. The integrated LED MODULE, which is available with different light colours (2700 K/3000 K) and a beam angle of 38°, provides lighting design options. Thanks to protection class IP 65, the recessed spotlight is also the ideal choice for damp rooms. In black or white, the round housing blends harmoniously into any room ambience. And thanks to the 68 mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

Item no.	1007407
IP Code	IP20/IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	200 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Lumen	570 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white

Light Source

869620		CRI	90
		Service life	50000 h
		Risk Group	1
		Height	5.85 cm
		Diameter	8.2 cm
		Net weight	0.246 kg
		Gross weight	0.287 kg
		Shape of cut-out	round
		Installation depth	6 cm
		Installation diameter	6.8 cm
		BIG WHITE Page	107