




NEW TRIA® UNIVERSAL 68

recessed ceiling light, 2500/3000/4000K, 60°, IP 20, square, white


Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® UNIVERSAL 68 are available as a complete set. Lighting design options are provided by the integrated multi-wattage LED MODULE, which is variable in terms of output and light intensity and available with different beam angles (38°/60°). While the CCT switch allows easy selection between 2500K, 3000K and 4000K, the pivot range ensures flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------------|
| Item no. | 1007439 |
| Rotating or tilting | Tilttable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 100-180 mA |
| Safety class | II |
| Wattage | 8.6 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 128 |
| Number of luminaires at LS C16A | 212 |
| Level of inrush current | 10 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.02 |
| Lumen | 540/600/600 lm |
| Colour temperature | 2500/3000/4000 Kelvin |
| Beam angle | 60 ° |
| Color | white |

Light Source

| | | | |
|---------|---|-----------------------|----------|
| 1807470 |  | CRI | 90 |
| | | LXXBXX data | L80B10 |
| | | Service life | 50000 h |
| | | Risk Group | 1 |
| | | Length | 8.2 cm |
| | | Width | 8.2 cm |
| | | Height | 3.4 cm |
| | | Net weight | 0.21 kg |
| | | Gross weight | 0.225 kg |
| | | Shape of cut-out | round |
| | | Installation depth | 4 cm |
| | | Installation diameter | 6.8 cm |
| | | BIG WHITE Page | 137 |