




## SURFACE V 390

10/15/20W 830/840 IP44


Discover our new technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the high-quality designed SURFACE V wall-mounted light, which is optionally available with a motion sensor. The light colour (3000-K/4000K) and light intensity (1850lm/2000lm) can be easily adjusted via dip switches. With a large beam angle of 120°, it homogeneously illuminates any environment, and its service life of 50,000 hours makes it ideal for long-term use. And the removable cover also makes installation easy. Decide in favour of SLVtec today.



## TECHNICAL DATA

Item no.	1007516
IP Code	IP 44
Assembly	Surface
Assembly details	Ceiling, Wall
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	165/120/84 mA
Safety class	I
Wattage	20 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	13
Number of luminaires at LS C16A	22
Level of inrush current	25.4 A
Duration of inrush current	200 µs
Stroboscopic effect (SVM)	0.4
Lumen	1850/2000 lm
Colour temperature	3000/4000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L80B10

## Light Source

771797		Service life	50000 h
		Height	11.5 cm
		Diameter	39 cm
		Net weight	0.74 kg
		Gross weight	1.34 kg