




D-RING S

wall light, PHASE, 2700/3000K, PHASE, IP65, black

The new D-RING family elegantly picks up on the trend towards organic shapes. The dimmable indirect warm white light (2700K / 3000K), which can be adjusted via a CCT switch, discreetly and glare-free sets the scene for the facades. The two different diameters offer plenty of creative scope. Thanks to the special surface treatment, it can also be used near the coast.



TECHNICAL DATA

Item no.	1007911
IP Code	IP65
Impact resistance class	IK 06
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Number of through-wires	160
Primary nominal voltage	220-240V ~50Hz
Secondary power / voltage	95 mA
Safety class	I
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	213
Number of luminaires at LS C16A	213
Level of inrush current	3.44 A
Duration of inrush current	48.4 µs
Stroboscopic effect (SVM)	0.01
Lumen	630/650 lm
Colour temperature	2700/3000 Kelvin
Color	black

Light Source

1907086		CRI	80
		LXXBXX data	L80B20
		Service life	50000 h
		Risk Group	1
		Depth	5 cm
		Diameter	16 cm
		Net weight	0.5 kg
		Gross weight	0.535 kg