




ONE VERTICAL PD

pendant light, 180cm, 2700/3000K, PHASE, black



Elegance meets modern technology. ONE VERTICAL PD PHASE boasts an unusual design: the vertically arranged rings of different sizes interlock artfully and create an extraordinary eye-catcher in the room. With a CRI>90 and a selectable light colour of 2700K or 3000K (CCT switch), the LED pendant light provides high-quality light. The dimming function gives every room the desired atmosphere, ideal for private living spaces and smaller projects. As part of the ONE family, ONE VERTICAL PD PHASE fits seamlessly into current design trends.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------------|
| Item no. | 1008002 |
| IP Code | IP20 |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1050 mA |
| Safety class | I |
| Wattage | 40 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 57 |
| Number of luminaires at LS C16A | 57 |
| Level of inrush current | 5 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 2400/2550 lm |
| Colour temperature | 2700/3000 Kelvin |
| Color | black |
| CRI | 90 |
| LXXBXX data | L80B10 |

Light Source

| | |
|---------|---|
| 1907084 |  |
| 1907085 |  |

| | |
|----------------|----------|
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 3 cm |
| Diameter | 80 cm |
| Pendant length | 180 cm |
| Net weight | 3.23 kg |
| Gross weight | 3.456 kg |