

Set consisting of 12 x UNIVERSAL DOWN-LIGHT PHASE IP20 38°

fixed/pivoting, without cover

Many qualities in one-this is how the SLV UNIVERSAL DOWNLIGHT is designed. The colour temperature can be quickly adjusted in four stages via CCT switch. The choice of 5 W or 7 W output is just as simple. And thanks to the lockable springs and Quick Connector Box, the downlight is quick and easy to install. In addition, the separately available covers in round or square and various colours allow the UNIVERSAL DOWNLIGHT to be used as a fixed downlight with IP65 or as a swivelling downlight with IP20.

TECHNICAL DATA

Item no.	1008066
Rotating or tilting	tiltable
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	60/85 mA
Safety class	II
Wattage	7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	80
Number of luminaires at LS C16A	200
Level of inrush current	3 A
Duration of inrush current	30 µs
Lumen	670/680/690/680 lm
Colour temperature	2700/3000/4000/6500 Kelvin
Beam angle	38 °
Color	black

Light Source

2093260	

Accessories

1007191	UNIVERSAL DOWNLIGHT cover , for downlight IP20, pivoting, round, gold matt
1008069	UNIVERSAL DOWNLIGHT cover , for Downlight, IP65, round, aluminium
1008096	UNIVERSAL DOWNLIGHT cover , for downlight, IP65, square, black
1008068	UNIVERSAL DOWNLIGHT cover , for Downlight, IP65, round, white
1008098	UNIVERSAL DOWNLIGHT cover , for downlight, IP65, square, gold matt
1008067	UNIVERSAL DOWNLIGHT cover , for Downlight IP65, round, black
1007186	UNIVERSAL DOWNLIGHT cover , for downlight IP20, pivoting, square, aluminium
1007091	UNIVERSAL DOWNLIGHT Cover , for Downlight IP20, pivoting, round, black
1008070	UNIVERSAL DOWNLIGHT cover , for downlight, IP65, round, gold matt
1008097	UNIVERSAL DOWNLIGHT cover , for downlight, IP65, square, aluminium
1007093	UNIVERSAL DOWNLIGHT Cover , for Downlight IP20, pivoting, round, aluminium
1007194	UNIVERSAL DOWNLIGHT cover , for downlight IP20, pivoting, square, gold matt
1007185	UNIVERSAL DOWNLIGHT cover , for downlight IP20, pivoting, square, white
1007092	UNIVERSAL DOWNLIGHT Cover , for Downlight IP20, pivoting, round, white

CRI	90
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8.5 cm
Net weight	2.976 kg
Gross weight	3.496 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	6.8 cm
BIG WHITE Page	1011

1008095	UNIVERSAL DOWN-LIGHT cover , for down-light, IP65, square, white
1007184	UNIVERSAL DOWN-LIGHT cover , for down-light IP20, pivoting, square, black