




RASTERLYSPOLE 70

free-standing lamp, 2700/3000 K, IP65, rectangular, anthracite

The RASTERLYS series combines modern design with high functionality. Whether mounted as a single light or in a row - the wall and bollard lights not only provide effective illumination, but also make an aesthetic statement on façades, entrances, terraces or in outdoor areas of catering establishments.with warm white light (2,700 K / 3,000 K via CCT switch), they create atmospheric accents in outdoor areas. Thanks to its IP65 and salt air-resistant surface, RASTERLYS is particularly robust and durable. The Triac dimming function and the loop-in/loop-out connection enable flexible and efficient installation.



TECHNICAL DATA

Item no.	1008385
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Ground
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	27 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	28
Number of luminaires at LS C16A	59
Level of inrush current	10 A
Duration of inrush current	300 µs
Temperature at glass (light emission)	60 °C
Lumen	700 / 750 lm
Colour temperature	2700/3000 Kelvin

Light Source

2166513	

Accessories

228726	Y-CONNECTION BOX , black, IP68
228730	CONNECTION BOX , 3-pin, IP68

Beam angle	70 °
Color	anthracite
CRI	80
Service life	50000 h
Risk Group	1
Length	17 cm
Width	10 cm
Height	70.2 cm
Net weight	2.7 kg
Gross weight	3.3 kg
BIG WHITE Page	731