


OCULUS

surface-mounted ceiling light, round, 2000-3000K, 11-W, dim-to-warm, PHASE, 100°, brass

With a high colour rendering index (CRI>90) and the option of dim-to-warm dimming for an especially warm light, every member of the OCULUS family can conjure up a unique lighting mood. The special lens optics provide a sharply contoured lighting effect, making this light perfect for accent lighting in sophisticated homes, medical practices, law firms, cafés, hotels and restaurants. By using the included frosted shade, the light can also be adjusted to provide diffuse light distribution rather than sharply contoured lighting. In addition to the classic black and white versions, all OCULUS lights are also available in three other elegant colours. The high-quality PVD coating ensures outstanding surface properties.



TECHNICAL DATA

Item no.	1008619
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	11 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	12.4 A
Duration of inrush current	7.2 µs
Lumen	36-780 lm
Colour temperature	2000-3000 Kelvin
Color	brass
CRI	90
Service life	40000 h
Risk Group	1
Height	9 cm

Diameter	9 cm
Net weight	0.57 kg
Gross weight	0.72 kg