


# DOWNLIGHT C

**DALI 150 20W 930 IP54**

Discover our technical product range: SLVtec. With state-of-the-art LED technology, we offer energy-efficient and functional lighting solutions for indoor and outdoor use. From wet room lights to high-bay spotlights – our high-quality products impress with functionality and a fair price-performance ratio. These include the DOWNLIGHT C recessed luminaires, which are ideal for general lighting in commercial environments. They are available in two different cut-outs (150 mm and 200 mm) and offer a colour temperature of 3000K or 4000K. You can also choose from an on/off version with switchable system output and a DALI-controllable version. With their eligible energy efficiency and a lumen output of up to 3,100 lm, you can experience sustainable lighting in commercial spaces.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008625 |
| **IP Code** | IP54 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Dimmable** | Yes |
| **Dimming technology** | DALI |
| **Number of through-wires** | 18 |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 500 mA |
| **Safety class** | II |
| **Wattage** | 20 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 18 |
| **Number of luminaires at LS C16A** | 39 |
| **Level of inrush current** | 15 A |
| **Duration of inrush current** | 300 µs |
| **Lumen** | 2250 lm |
| **Colour temperature** | 3000 Kelvin |
| **Color** | white |
| **CRI** | 90 |

| | |
|---|---|
| **UGR ≤** | 22 |
| **Service life** | 70000 h |
| **Height** | 8.6 cm |
| **Diameter** | 17.6 cm |
| **Net weight** | 0.5 kg |
| **Gross weight** | 0.6 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 9 cm |
| **Installation diameter** | 15.5 cm |