


MEDO® 30

recessed ceiling light, frameless, 3000/4000K, 70°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frameless. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



TECHNICAL DATA

Item no.	1008630
IP Code	IP20
Assembly	Recessed
Secondary power / voltage	250 mA
Safety class	III
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Lumen	1150/1200 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	9.5 cm
Diameter	28 cm
Net weight	0.9 kg
Gross weight	2.36 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	29 cm

Accessories

1006871	NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / white
1006870	NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / black
1008673	Strain relief through-wirable , for DALI dimmable drivers: 1008666, 1008667, 1008668
1008672	Strain relief , standard, for DALI-dimmable drivers: 1008666, 1008667, 1008668
1008699	
1008660	LED driver 10W 180-270-mA , PHASE
1008666	LED driver 15W , 100-700mA, DALI