


MEDO® 60

recessed ceiling light, frameless, 3000/4000K, 80°, IP20, round, white

The best MEDO® of all time is also available as a recessed ceiling light in four different sizes, including frame or frameless. It impresses with a longer service life and subsidised energy efficiency of over 140 lm/W. The colour rendering index CRI>90 ensures true-colour and, with UGR<19, virtually glare-free light quality, making it suitable for use in offices. The CCT switch enables you to choose between 3000 K and 4000 K, letting you personalise your lighting situation. Please note that the driver and strain relief must be purchased separately.



TECHNICAL DATA

Item no.	1008634
IP Code	IP20
Assembly	Recessed
Secondary power / voltage	1000 mA
Safety class	III
Wattage	33 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Lumen	4600/4600 lm
Colour temperature	3000/4000 Kelvin
Color	white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	12.5 cm
Diameter	60 cm
Net weight	4.4 kg
Gross weight	8 kg
Shape of cut-out	round
Installation depth	16 cm
Installation diameter	61 cm

Accessories

1008669	LED driver 53W , 650-1400mA, DALI
1008701	
1006871	NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / white
1006870	NUMINOS® PROJECTOR XS , recessed ceiling light, 2700 K, 40°, cylindrical, black / black
1008674	Strain relief standard , for DALI dimmable drivers: 1008669
1008665	LED driver 40W , 700-1050mA, PHASE
1008702	