


# NOBLO®

**wall and ceiling-mounted light, single, round, 2000-3000K, 8W, dim-to-warm, PHASE, 36°, white**

Discover the technical upgrade of the NOBLO® spotlights, which impress with their slimline design. The rotating and swivelling spotlights are ideal for both wall and ceiling mounting. With two timeless housing colours and one, two or three light outlets, they can be used flexibly. The NOBLO® spotlights are available with 2700K, 3000K or as a dim-to-warm version for customised lighting design. Additional visual accents can be created with the separately available decorative rings.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1008703 |
| **Number of different light outlets** | 1 |
| **IP Code** | IP20 |
| **Assembly** | Surface |
| **Dimmable** | Yes |
| **Dimming technology** | trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 350 |
| **Safety class** | I |
| **Wattage** | 8 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 224 |
| **Number of luminaires at LS C16A** | 266 |
| **Level of inrush current** | 5 A |
| **Duration of inrush current** | 100 µs |
| **Lumen** | 10-450 lm |
| **Colour temperature** | 2000-3000 Kelvin |
| **Color** | white |
| **CRI** | 90 |
| **Service life** | 40000 h |
| **Risk Group** | 1 |

| | |
|---|---|
| **Length** | 9 cm |
| **Width** | 10.5 cm |
| **Height** | 12.7 cm |
| **Net weight** | 0.31 kg |
| **Gross weight** | 0.42 kg |

## Accessories

| | |
|---|---|
| 1008484 | NOBLO® , decorative ring, gold |
| 1008487 | NOBLO® , decorative ring, bronze |
| 1008486 | NOBLO® , decorative ring, copper |
| 1008483 | NOBLO® , decorative ring, white |
| 1008482 | NOBLO® , decorative ring, black |
| 1008485 | NOBLO® , decorative ring, grey |