

48V SYSTEM

Intrack LED driver, 48VDC, 250 W, Incl. 300 cm connection cable for 220-240VAC and DALI through-wiring, BlackWhite

Maximum minimalism and simple elegance: with an output of up to 250 watts, the LED driver is designed for flexible use in the 48V TRACK mounting tracks. Thanks to the four-wire 220V-240V / DALI through-wiring, controllable lighting concepts with particularly small tracks and spotlights are easy to realise. The 3-metre cable supplied offers additional flexibility - ideal if the 48V rails are to be suspended.

TECHNICAL DATA

Item no.	1009001
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	48 V
Safety class	II
Safety class	II
Wattage	272 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	12
Number of luminaires at LS C16A	19
Level of inrush current	80 A
Duration of inrush current	200 µs
Color	white
Length	26.8 cm
Width	2.2 cm
Height	4.35 cm
Net weight	0.384 kg
Gross weight	0.413 kg

BIG WHITE Page	471