


# NEW TRIA® 68

**recessed ceiling light, PHASE, AIRTIGHT, round, 2700 K, 7.5 W, white**

Discover the new generation of our NEW TRIA® recessed ceiling light. The NEW TRIA® 68 models are now also available in an airtight version, making them ideal for applications with increased airtightness requirements. The integrated LED module, available in 2,700K or 3,000K depending on the version, ensures maximum lighting design freedom. The high quality recessed light in black or white blends discreetly and stylishly into any ceiling.




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009020 |
| **IP Code** | IP20/IP23 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Dimmable** | Yes |
| **Dimming technology** | Leading edge,trailing edge |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 180 mA |
| **Safety class** | II |
| **Wattage** | 7.5 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 35 °C |
| **Number of luminaires at LS B16A** | 88 |
| **Number of luminaires at LS C16A** | 149 |
| **Level of inrush current** | 3 A |
| **Duration of inrush current** | 30 µs |
| **Lumen** | 591 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 38 ° |
| **Color** | white |

## Light Source

| | |
|---|---|
| 869193 |  |

| | |
|---|---|
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **Service life** | 50000 h |
| **Height** | 5.1 cm |
| **Diameter** | 8.2 cm |
| **Net weight** | 0.21 kg |
| **Gross weight** | 0.24 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 4.8 cm |
| **Installation diameter** | 6.8 cm |
| **BIG WHITE Page** | 71 |