
NUMINOS® XS

Recessed ceiling light, 3000 K, 20°, IP20, round, black

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009289
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	950 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	4.5 cm
Diameter	6.5 cm
Net weight	0.1 kg
Gross weight	0.2 kg

Light Source

2093745	

Accessories

1005614	NUMINOS® XS , frosted diffuser
1010126	NUMINOS® XS , reflector, copper
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1010125	NUMINOS® XS , reflector, gold
1005613	NUMINOS® XS , transparent diffuser

Shape of cut-out	round
Installation depth	11 cm
Installation diameter	5.5 cm