
Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When will you choose SLV's modular variety?




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009339 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 6.9 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 900 lm |
| **Colour temperature** | 2700 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | white/chrome |
| **CRI** | 90 |
| **UGR ≤** | 22 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 5.3 cm |
| **Diameter** | 8 cm |
| **Net weight** | 0.11 kg |

## Light Source

| | |
|---|---|
| 2093755 |  |

## Accessories

| | |
|---|---|
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1010695 | LED driver , 21W, 200 mA, DALI |
| 1010703 | LED driver , 23W, 200 mA, DALI |
| 1005612 | NUMINOS® XS , diffuser |
| 1010699 | LED driver , 10W, 200 mA, PHASE |
| 1005615 | NUMINOS® XS , black diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1010126 | NUMINOS® XS , reflector, copper |
| 1010125 | NUMINOS® XS , reflector, gold |

| | |
|---|---|
| **Gross weight** | 0.22 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 8 cm |
| **Installation diameter** | 6.8 cm |