
NUMINOS® GIMBLE S

Recessed ceiling light, 4000 K, 55°, IP20, round, black

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® GIMBLE S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009421
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1050 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	7 cm
Diameter	10 cm
Net weight	0.188 kg

Light Source

2093742	

Accessories

1010128	NUMINOS® S , reflector, copper
1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honey-comb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1010127	NUMINOS® S , reflector, gold
1010680	NUMINOS® S , Prismatic diffuser

Gross weight	0.288 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	9 cm