
NUMINOS® MOVE S

Recessed ceiling light, 3000 K, 55°, IP20, round, black / white

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® MOVE S recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009512
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.7 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1050 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black/white
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	6.35 cm
Diameter	10 cm
Net weight	0.188 kg

Light Source

2093839	

Accessories

1010128	NUMINOS® S , reflector, copper
1010681	NUMINOS® S , frosted diffuser
1010682	NUMINOS® S , Elliptical diffuser
1010679	NUMINOS® S , Honey-comb diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1010699	LED driver , 10W, 200 mA, PHASE
1010127	NUMINOS® S , reflector, gold
1010680	NUMINOS® S , Prismatic diffuser

Gross weight	0.288 kg
Shape of cut-out	round
Installation depth	8.5 cm
Installation diameter	9 cm