
NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® MOVE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?




## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1009519 |
| **Number of different light outlets** | 1 |
| **Rotating or tilting** | rotary bar and tiltable |
| **IP Code** | IP20 |
| **Assembly** | Recessed |
| **Assembly details** | Ceiling |
| **Secondary power / voltage** | 200 mA |
| **Safety class** | III |
| **Wattage** | 6.7 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Lumen** | 1050 lm |
| **Colour temperature** | 3000 Kelvin |
| **Beam angle** | 40 ° |
| **Color** | white/chrome |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **Service life** | 50000 h |
| **Risk Group** | 1 |
| **Height** | 6.35 cm |
| **Diameter** | 10 cm |
| **Net weight** | 0.188 kg |

## Light Source

| | |
|---|---|
| 2093839 |  |

## Accessories

| | |
|---|---|
| 1010681 | NUMINOS® S , frosted diffuser |
| 1010682 | NUMINOS® S , Elliptical diffuser |
| 1010679 | NUMINOS® S , Honey-comb diffuser |
| 1010695 | LED driver , 21W, 200 mA, DALI |
| 1010703 | LED driver , 23W, 200 mA, DALI |
| 1010699 | LED driver , 10W, 200 mA, PHASE |
| 1010680 | NUMINOS® S , Prismatic diffuser |
| 1010128 | NUMINOS® S , reflector, copper |
| 1010127 | NUMINOS® S , reflector, gold |

| | |
|---|---|
| **Gross weight** | 0.288 kg |
| **Shape of cut-out** | round |
| **Installation depth** | 8.5 cm |
| **Installation diameter** | 9 cm |