
NUMINOS® GIMBLE M

Recessed ceiling light, 4000 K, 20°, black / white

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® GIMBLE M recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009578
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1900 lm
Colour temperature	4000 Kelvin
Beam angle	20 °
Color	black/white
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	9.5 cm
Diameter	13.5 cm
Net weight	0.41 kg

Light Source

2093752	

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010129	NUMINOS® M , reflector, gold
1010683	NUMINOS® M , Honey-comb diffuser
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prisma-tic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1010130	NUMINOS® M , reflector, copper

Gross weight	0.56 kg
Shape of cut-out	round
Installation depth	9.5 cm
Installation diameter	12 cm