
The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® DL M recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 12 watts, a luminous flux of 1800 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009627
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	350 mA
Safety class	III
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1800 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white/chrome
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	6.8 cm
Diameter	10.5 cm
Net weight	0.22 kg
Gross weight	0.28 kg

Light Source

2093856	

Accessories

1010704	LED driver , 23W, 350 mA, DALI
1010700	LED driver , 20W, 350 mA, PHASE
1010683	NUMINOS® M , Honey-comb diffuser
1010686	NUMINOS® M , Elliptical diffuser
1010684	NUMINOS® M , Prisma-tic diffuser
1010696	LED driver , 21W, 350 mA
1010685	NUMINOS® M , frosted diffuser
1010129	NUMINOS® M , reflector, gold
1010130	NUMINOS® M , reflector, copper

Shape of cut-out	round
Installation depth	7.5 cm
Installation diameter	9 cm