
Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. The different downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17 watts, luminous flux of 2500 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1009782
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2500 lm
Colour temperature	3000 Kelvin
Beam angle	55 °
Color	black/chrome
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.434 kg
Gross weight	0.584 kg

Light Source

2093856	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010705	LED driver , 36W, 500 mA, DALI
1010132	NUMINOS® L , reflector, copper
1010131	NUMINOS® L , reflector, gold

Shape of cut-out	round
Installation depth	8.5 cm
Installation diameter	12 cm