
NUMINOS® L

Recessed ceiling light, 4000 K, 40°, IP20, round, black / white

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINOS® DL L recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2700 lumens, a colour temperature of 4000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009796
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2700 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	black/white
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	8.5 cm
Diameter	13 cm
Net weight	0.44 kg
Gross weight	0.59 kg

Light Source

2093752	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010132	NUMINOS® L , reflector, copper
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010131	NUMINOS® L , reflector, gold
1010705	LED driver , 36W, 500 mA, DALI

Shape of cut-out	round
Installation depth	8.5 cm
Installation diameter	12 cm