
The NUMINOS light system from SLV perfectly combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® MOVE DL L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light has a power consumption of 17 watts, a luminous flux of 2400 lumens, a colour temperature of 2700 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009819
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	500 mA
Safety class	III
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	2400 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white/black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	9.3 cm
Diameter	16 cm
Net weight	0.51 kg

Light Source

2093870	

Accessories

1010689	NUMINOS® L , Frosted diffuser
1010697	LED driver , 21W, 500 mA
1010687	NUMINOS® L , Honey-comb diffuser
1010701	LED driver , 19 W, 500 mA, PHASE
1010688	NUMINOS® L , Prismatic diffuser
1010690	NUMINOS® L , Elliptical diffuser
1010705	LED driver , 36W, 500 mA, DALI
1010132	NUMINOS® L , reflector, copper
1010131	NUMINOS® L , reflector, gold

Gross weight	0.66 kg
Shape of cut-out	round
Installation depth	10.5 cm
Installation diameter	14.5 cm