
The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1010074
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	1000 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	white/black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.11 kg

Light Source

2093754	

Accessories

1005614	NUMINOS® XS , frosted diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1005613	NUMINOS® XS , transparent diffuser
1010126	NUMINOS® XS , reflector, copper
1010125	NUMINOS® XS , reflector, gold

Gross weight	0.21 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm