

# 48V SYSTEM

**Intrack LED driver, 48VDC, 100 W, incl. 300 cm connection cable for 220-240VAC and DALI through-wiring, black**

Maximum minimalism and simple elegance: with an output of up to 100 watts, the LED driver is designed for flexible use in the 48V TRACK mounting tracks. Thanks to the four-wire 220V-240V / DALI through-wiring, controllable lighting concepts with particularly small tracks and spotlights are easy to realise. The 3-metre cable supplied offers additional flexibility - ideal if the 48V rails are to be suspended.

## TECHNICAL DATA

| | |
|---|---|
| **Item no.** | 1010446 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK 02 |
| **Impact resistance** | 0.2 Joule |
| **Assembly details** | Ceiling,Wall |
| **Primary nominal voltage** | 220-240V ~50/60 Hz |
| **Secondary power / voltage** | 48 V |
| **Safety class** | II |
| **Safety class** | II |
| **Wattage** | 115 W |
| **Minimum ambient temperature** | -20 °C |
| **Maximum ambient temperature** | 40 °C |
| **Number of luminaires at LS B16A** | 16 |
| **Number of luminaires at LS C16A** | 26 |
| **Level of inrush current** | 60 A |
| **Duration of inrush current** | 200 µs |
| **Color** | black |
| **Length** | 29.75 cm |
| **Width** | 1.6 cm |
| **Height** | 1.9 cm |
| **Net weight** | 0.332 kg |
| **Gross weight** | 0.36 kg |

| | |
|---|---|
| **BIG WHITE Page** | 471 |