




## NEW TRIA 1 recessed fitting

single-headed, QPAR51, round, brushed aluminium, max. 50W, incl. clip springs

The round, high-voltage version of our popular NEW TRIA recessed fitting series is available with black, white or brushed aluminium housings. The generous rotation and pivoting range of this recessed spot guarantees you the ability to individually focus its light beam, regardless of whether you choose to use halogen or LED retrofit lamps. Installation is carried out using the factory installed spring clips. The NEW TRIA 1 recessed fitting is supplied ready for direct connection to the 230V alternating current.



## TECHNICAL DATA

Item no.	111360
Socket	GU10
Number of sockets	1
Tilt range	30 °
Horizontal rotation range	360 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	50 W
Color	aluminium
Light outlet	direct
Height	11 cm
Diameter	9.3 cm
Net weight	0.167 kg
Gross weight	0.205 kg
Shape of cut-out	round
Installation depth	12.5 cm
Installation diameter	7.8 cm

**Recommended lamp**

1005075	LED lightbulb QPAR51 , GU10, 2700K, grey
1005081	LED lightbulb QPAR51 , GU10, 4000K, grey
1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005078	LED lightbulb QPAR51 , GU10, 3000K, grey