




NEW TRIA 1

recessed fitting, single-headed, QPAR51, round, white, max. 50W, incl. leaf springs

The round, high-voltage version of our popular NEW TRIA recessed fitting series is available with black, white or brushed aluminium housings. The generous rotation and pivoting range of this recessed spot guarantees you the ability to individually focus its light beam, regardless of whether you choose to use halogen or LED retrofit lamps. Installation is carried out using the factory installed leaf springs. The NEW TRIA recessed fitting is supplied ready for direct connection to the 230V alternating current.



TECHNICAL DATA

Item no.	111711
Socket	GU10
Number of sockets	1
Tilt range	30 °
Horizontal rotation range	360 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	50 W
Color	white
Light outlet	direct
Height	11.5 cm
Diameter	9.3 cm
Net weight	0.184 kg
Gross weight	0.222 kg
Shape of cut-out	round
Installation depth	13 cm
Installation diameter	7.8 cm

Recommended lamp

1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005079	LED lightbulb QPAR51 , GU10, 3000K, white
1005076	LED lightbulb QPAR51 , GU10, 2700K, white
1005082	LED lightbulb QPAR51 , GU10, 4000K, white