




DL 126

recessed fitting, LED SMD, 3000K, round, chrome, max. 3W, incl. leaf springs

The DL 126 recessed fitting impresses with its low height and it is therefore ideal for use with low installation depths. The six long-life SMD LEDs with a total power output of 3W ensure that you have the necessary level of illumination. The recessed fitting is available with a shutter coloured white, chrome and brushed metal. A suitable 12V direct current power supply is needed for operation. This luminaire contains built-in warm-white LED lamps.



TECHNICAL DATA

Item no.	112222
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling, Wall
Primary nominal voltage	12V
Safety class	III
Wattage	2.8 W
Lumen	170 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	chrome
CRI	80
LXXBXX data	L70B50
Service life	60000 h
Risk Group	0
Height	1.6 cm
Diameter	6.5 cm
Net weight	0.11 kg
Gross weight	0.128 kg
Shape of cut-out	round
Installation depth	1.4 cm
Installation diameter	5.7 cm

Light Source

916556		BIG WHITE Page	227
--------	---	----------------	-----

Accessories

1005381	LED Power supply , 20W 12/24V
1005444	LED Power supply , 15W 12V
112182	INSTALLATION FRAME , for DL 126 recessed fittin- g, round, chrome
112185	INSTALLATION FRAME , for DL 126 recessed fittin- g, round, brushed metal