




VERLUX

recessed fitting, LED, 3000K, matt white, L/B/T
19/19/10 cm, 28W


The light, square recessed VERLUX fitting with a round cut-out is available in various wattages and sizes. The square recessed ceiling light is made of aluminium and comes in a white colour. The rigid Premium LED insert produces homogeneous base lighting thanks to its wide beam angle of 80°. The luminaire comes with a dimmable constant current driver and is ready for connection to the 230 V mains supply.



TECHNICAL DATA

Item no.	112702
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	31 W
Rated standby power	0.5 W
Level of inrush current	8 A
Duration of inrush current	25 µs
Stroboscopic effect (SVM)	0.02
Lumen	2360 lm
Colour temperature	3000 Kelvin
Beam angle	80 °
Color	white
CRI	80

Light Source

916454		LXXBXX data	L70B50
		Service life	35000 h
		Light distribution	rotational symmetric
		Light outlet	direct
		Length	19 cm
		Width	19 cm
		Depth	10 cm
		Net weight	0.623 kg
		Gross weight	0.835 kg
		Shape of cut-out	round
		Installation depth	10 cm
		Installation diameter	17.5 cm