




## FRAME BASIC

recessed fitting, LED, 3000K, matt black, SET, 9.4W, incl. driver


With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED set is equipped with warm white Premium LED light diodes. This luminaire contains built-in LED lamps.



## TECHNICAL DATA

Item no.	112720
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	50 °C
Level of inrush current	11 A
Duration of inrush current	20 µs
Stroboscopic effect (SVM)	0.02
Lumen	600 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	50000 h
Length	9 cm
Width	9 cm

Light Source

916629		Height	4 cm
		Net weight	0.172 kg
		Gross weight	0.215 kg
		Shape of cut-out	square
		Installation length	7.5 cm
		Installation width	7.5 cm
		Installation depth	5 cm
		BIG WHITE Page	238