




NEW TRIA 68 I CS

Indoor LED recessed ceiling light alu round 3000K 38°
incl. driver clip springs


The simplicity and effectiveness of the innovative NEW TRIA 1 SET is captivating. It is available in white or brushed aluminium, and in round or square form. Equipped with one powerful, warm white premium COB LED, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. Furthermore, it is adjustable by 38°. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 113956 |
| Rotating or tilting | tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 100-240V ~50/60Hz |
| Secondary power / voltage | 350 mA |
| Safety class | II |
| Wattage | 4 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Level of inrush current | 10 A |
| Duration of inrush current | 92 µs |
| Stroboscopic effect (SVM) | 0.01 |
| Lumen | 360 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 38 ° |
| Color | aluminium |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 40000 h |
| Risk Group | 0 |

Light Source

| | | | |
|--------|---|-----------------------|----------|
| 916559 |  | Height | 3.5 cm |
| | | Diameter | 8.2 cm |
| | | Net weight | 0.196 kg |
| | | Gross weight | 0.239 kg |
| | | Shape of cut-out | round |
| | | Installation depth | 3.5 cm |
| | | Installation diameter | 6.8 cm |