




NEW TRIA 1 SET recessed fitting

LED, 2700K, round, white, 30°, 29W incl. driver, clip springs


The simplicity and effectiveness of the NEW TRIA 1 SET is captivating. It is available in black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	114261
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	29 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.33 W
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	2500 lm
Colour temperature	2700 Kelvin
Beam angle	30 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h

Light Source

916519		Height	9.5 cm
		Diameter	18 cm
		Net weight	0.857 kg
		Gross weight	1.004 kg
		Shape of cut-out	round
		Installation depth	10 cm
		Installation diameter	15 cm