




NEW TRIA MINI SET

recessed fitting, Power LED, 3000K, square, matt white, 30°, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA MINI Set is captivating. It is available in matt black, matt white, or brushed aluminium, and in round or square form. Equipped with a powerful, warm white premium LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	114401
Rotating or tilting	tiltable
IP Code	IP 20 / IP 44
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	3.4 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	15 A
Duration of inrush current	150 µs
Stroboscopic effect (SVM)	0
Lumen	190 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	white
CRI	90
UGR ≤	19
LXXBXX data	L70B50

Light Source



Service life	30000 h
Risk Group	1
Length	5.2 cm
Width	5.2 cm
Height	3.6 cm
Net weight	0.115 kg
Gross weight	0.141 kg
Shape of cut-out	round
Installation depth	4 cm
Installation diameter	4.5 cm