




## PATTA-F

recessed fitting, LED, 3000K, round, white, 38°, incl. driver


The innovative PATTA F recessed fitting is suitable for ceiling thicknesses of up to 20 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in black, white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



## TECHNICAL DATA

Item no.	114441
IP Code	IP 20 / IP 65
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	11 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	860 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	6.2 cm

Light Source

916451		Diameter	8.3 cm
		Net weight	0.309 kg
		Gross weight	0.384 kg
		Shape of cut-out	round
		Installation depth	6 cm
		Installation diameter	7 cm
		BIG WHITE Page	246