




H-LIGHT 1

recessed fitting, LED, 2700K, round, black, 20°, 11,5W, incl. driver, clip spring

The H-LIGHT 1 recessed fitting series impresses with its simple and elegant design, the integrated warm-white LED module with its narrow 20° beam angle ensures a discreet and ambience-oriented radiance. Thanks to the LED driver included in the set, the luminaire is immediately ready for connection to a 230V power supply.



TECHNICAL DATA

Item no.	114480
Rotating or tilting	tiltable
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	II
Wattage	11 W
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	265 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	8 cm

Light Source

916341	
--------	---

Diameter	9 cm
Net weight	0.328 kg
Gross weight	0.381 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	8 cm
BIG WHITE Page	232