




## KADUX 2 SET

recessed fitting, double-headed LED, 3000K, rectangular, matt black, 38°, 15W, incl. driver


The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 2 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



## TECHNICAL DATA

Item no.	115710
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	2 A
Duration of inrush current	80 µs
Stroboscopic effect (SVM)	0.01
Lumen	1290 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50

## Light Source

916451	
Service life	40000 h
Length	15 cm
Width	9 cm
Height	8.5 cm
Net weight	0.541 kg
Gross weight	0.61 kg
Shape of cut-out	square
Installation length	14 cm
Installation width	8 cm
Installation depth	8 cm