




## KADUX 1 SET

recessed fitting, single-headed LED, 3000K ex, square, matt black, 30°, 29W, incl. driver, clip springs

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This XL Type LED Set is multi-directional, allowing individual focus of the light beam. Its high output, warm white Premium COB LED produces exceptionally powerful illumination. The KADUX 1 SET recessed fitting comes ready for direct connection to 230V mains.



## TECHNICAL DATA

Item no.	115730
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	29 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	35 °C
Network rated standby power	0.33 W
Level of inrush current	15 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0
Lumen	2700 lm
Colour temperature	3000 Kelvin
Beam angle	30 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	30000 h

Light Source

916475	
--------	---

Length	19.5 cm
Width	19.5 cm
Height	12.5 cm
Net weight	1.575 kg
Gross weight	1.952 kg
Shape of cut-out	square
Installation length	17 cm
Installation width	17 cm
Installation depth	12.5 cm