




KADUX 2 SET

recessed fitting, double-headed LED, 3000K xl, rectangular, matt black, 30°, 54W, incl. driver, clip springs

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This XL Type LED Set is multi-directional, allowing individual focus of the light beam. Its high output, warm white Premium COB LED produces exceptionally powerful illumination. The KADUX 2 SET recessed fitting comes ready for direct connection to 230V mains.



TECHNICAL DATA

| | |
|-----------------------------|-------------------|
| Item no. | 115740 |
| Rotating or tilting | cardanic |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 1400 mA |
| Safety class | II |
| Wattage | 54 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 35 °C |
| Network rated standby power | 0.41 W |
| Level of inrush current | 15 A |
| Duration of inrush current | 100 µs |
| Stroboscopic effect (SVM) | 0 |
| Lumen | 5200 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 30 ° |
| Color | black |
| CRI | 80 |
| LXXBXX data | L70B50 |
| Service life | 30000 h |

Light Source

| | |
|--------|---|
| 916475 |  |
|--------|---|

| | |
|---------------------|---------|
| Length | 37 cm |
| Width | 19.5 cm |
| Height | 12.5 cm |
| Net weight | 2.76 kg |
| Gross weight | 3.3 kg |
| Shape of cut-out | square |
| Installation length | 34.5 cm |
| Installation width | 17 cm |
| Installation depth | 12.5 cm |