




OCCULDAS 23

recessed fitting, LED, 3000K, round, white, 26W


The OCCULDAS 23 dimmable recessed ceiling light was designed exclusively by David Morgan and is fitted with a premium LED. The central trim ensures homogeneous, glare-free, atmospheric indirect lighting. Thanks to the built-in LED driver, the luminaire is suitable for direct connection to a 230V mains supply.



TECHNICAL DATA

Item no.	117311
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	23 W
Stroboscopic effect (SVM)	0.04
Lumen	1500 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	80
UGR ≤	28
LXXBXX data	L70B50
Service life	30000 h
Risk Group	1

Light Source

916572		Height	7.8 cm
		Diameter	22.6 cm
		Net weight	1.27 kg
		Gross weight	1.749 kg
		Shape of cut-out	round
		Installation depth	8.5 cm
		Installation diameter	20.5 cm
		BIG WHITE Page	230