




MEDO RING 60

pendant, LED, white, Ø 60 cm, incl. LED driver

As well as having an appealing design, the modern MEDO RING impresses with efficient and powerful LED modules that are also dimmable. The aluminium frame is fitted with an acrylic glass cover which provides bright and uniform illumination. Its 1.5 metre pendant length makes it ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



TECHNICAL DATA

Item no.	133841
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	33 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Rated standby power	0.5 W
Level of inrush current	6 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.13
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR ≤	22
LXXBXX data	L70B50
Service life	20000 h

Light Source

916532	
--------	---

Accessories

470505	EP1 DIMMER , 1-10V, max. 10W
--------	---------------------------------

Risk Group	1
Height	8 cm
Diameter	60 cm
Pendant length	150 cm
Net weight	4.915 kg
Gross weight	6.119 kg
BIG WHITE Page	167