# Specialist • Lighting • Vendor








### **MEDO 60**

ceiling light, LED, 3000K, round, white, Ø 60 cm, can be converted to a pendant, 40 W

The high-quality MEDO CL impresses with its clear design and the elegant synergy of the aluminium and glass materials that have been used. Thanks to having an integrated premium LED, it generates a bright and homogeneous light. The ceiling light can be converted into a pendant using a suspension kit, and is therefore also ideal for rooms with high ceilings. The built-in LED driver makes direct connection to a 120V to 240V mains supply possible.



#### **TECHNICAL DATA**

Item no.	135121
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	38 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Rated standby power	0.5 W
Level of inrush current	6 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.08
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	105 °
Color	white
CRI	80
UGR≤	22
LXXBXX data	L70B50
Service life	30000 h

# Specialist • Lighting • Vendor



## **Light Source**

916580	A D
Accessories	
1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Risk Group	1
Height	13 cm
Diameter	60 cm
Net weight	5.817 kg
Gross weight	8.094 kg