




## BIMA 2

spot for 240V 1-phase track, double-headed, QPAR51, silver-grey, max. 50W, incl. 1-phase adapter

Double-headed adjustable high-voltage spot BIMA 2 with suitable adapter for the 240V 1-phase track system. The luminaire is made of aluminium and has a GU10 socket installed which makes it suitable for both halogen and LED lamps. Both lamp heads are separately adjustable.



## TECHNICAL DATA

Item no.	143432
Socket	GU10
Number of sockets	2
Tilt range	200 °
Horizontal rotation range	350 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling, Track Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	50 W
Color	grey
Light outlet	direct
Length	8 cm
Height	14 cm
Diameter	6 cm
Net weight	0.4 kg
Gross weight	0.507 kg
BIG WHITE Page	519

**Recommended lamp**

1005075	LED lightbulb QPAR51 , GU10, 2700K, grey
1005081	LED lightbulb QPAR51 , GU10, 4000K, grey
1005273	QPAR51 GU10 , LED light, 6W 2200 2700K CRI90 36°
1005078	LED lightbulb QPAR51 , GU10, 3000K, grey