




DOWNUNDER PUR 80

recessed fitting, LED, 3000K, square, white, L/W/H 8/3.2/8 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER 80 series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 80 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 350mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	151950
IP Code	IP 20
Assembly	Recessed
Assembly details	Wall
Secondary power / voltage	350 mA
Safety class	III
Wattage	3.6 W
Lumen	180 lm
Colour temperature	3000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Service life	30000 h
Light distribution	symmetric
Light outlet	direct
Width	8 cm
Height	8 cm
Depth	3.2 cm
Net weight	0.126 kg
Gross weight	0.171 kg
Shape of cut-out	square
Installation length	7 cm

Light Source

916412	
--------	---

Accessories

111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
151960	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 80, L/H 14/14 cm
111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA
1007270	LED driver 3W , 350mA including AMP socket

Installation width	6.5 cm
Installation depth	3.5 cm
BIG WHITE Page	242