




ENOLA_C

ceiling light, LED, 3000K, round, white, 35°

The puristic ceiling mounted light ENOLA_C consists of a cylindrical aluminium construction and is equipped with a high-performance COB LED with warm white light colour. By the incorporated LED driver, the electrical connection is made directly to 230V mains supply. As an accessory for the cylindrical spot, we also offer suitable decorative rings with a textured glass diffuser. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	152101
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	11 W
Level of inrush current	4.7 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.01
Lumen	1020 lm
Colour temperature	3000 Kelvin
Beam angle	35 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Height	10.7 cm
Diameter	10 cm
Net weight	0.54 kg
Gross weight	0.65 kg

Light Source

916476	 The logo consists of a small square containing the letters 'A' and 'G' stacked vertically, followed by a yellow arrow pointing to the right with the letter 'E' inside it.	BIG WHITE Page	259
--------	--	----------------	-----